

Lenderink Technologies INC.

1267 House NE
Belmont, MI 49306
(616) 887-8257

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

MSDS A: Dribond® #600, #700, #800

Section I

Manufacturer's Name	Lenderink and Affiliate	Emergency Telephone Number	616-887-8257
Address (Number, Street, City, State, and ZIP Code)		Telephone Number for Information	616-887-8257
	1267 House Road NE	Date Prepared	9/26/03
	Belmont MI 49306 USA	Signature of Preparer (optional)	

Section II - Hazardous ingredients / Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
None of the components present in this material				
At concentrations equal to or greater than 0.1% are listed				
By IARC, NTP, OSHA, or ACGIH as a carcinogen				

Section III - Physical / Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	0.915-1.3
Vapor Pressure (mm Hg.)	NA	Melting Point	200-240 F
Vapor Density (AIR=1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	Negligible		
Appearance and Odor	MILD		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	NA -	Flammable Limits	NFPA:1	HMIS:1
Extinguishing Media	ALL EXTINGUISHING MEDIA MAY BE USED. WATER CAN BE USED, BUT IS NOT RECOMMENDED DUE TO POTENTIAL SPLATTERING OF MOLTEN POLYMER POTENTIALLY SPREADING THE FIRE.			

Section V - Reactivity Data

Stability	NA	Unstable		Conditions to Avoid
		Stable	X	
Incompatibility (Materials to avoid) NA				
Hazardous Decomposition or Byproducts NA				
Hazardous Polymerization	May Occur			Conditions to Avoid
	Will not Occur		X	

Section VI - Health Hazard Data

Route(s) of Entry:	NA	Inhalation?	NA	Skin?	NA	Ingestion?	NA
Health Hazards (Acute and Chronic) NA - NOT A HAZARDOUS MATERIAL							
Carcinogenicity:	NA	NTP?		IARC Monographs?		OSHA Regulated?	
Signs and Symptoms of Exposure NA							
Medical Conditions Generally Aggravated by Exposure NA							
Emergency and First Aid Procedures NA.							

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	Sweep or Scoop up and Remove
Waste Disposal Method	RECYCLE, INCINERATE, OR LANDFILL
STORING: all films have a shelf life, so whenever possible use materials shortly after they are received. Store out of direct sunlight and do not store near heat sources such as radiators or air vents.	
Other Precautions maximum 75 F ambient temperature; 45% relative humidity is ideal	

Section VIII - Control Measures

Respiratory Protection (Specify Type)			
Ventilation:	Local Exhaust	X	Special
	Flammable Limits		Other
Protective Gloves	NA	Eye Protection	SAFETY GLASSES PRUDENT
Other Protective Clothing or Equipment NA			
Work/Hygienic Practices Practice good industrial hygiene			