

# LENDERINK TECHNOLOGIES INC.

1267 House NE  
Belmont, MI 49306  
(616) 887-8257

Material Safety Data Sheet  
May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

U.S. Department of Labor  
Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

## MSDS E: Dribond® 100L, 360, 360L, 363L, 3615 Heat-activated Dry Film Adhesive

### Section I

Manufacturer's Name	Lenderink and Affiliate	Emergency Telephone Number	616-887-8257
Address (Number, Street, City, State, and ZIP Code)		Telephone Number for Information	616-887-8257
	1267 House Road NE	Date Prepared	01/01/2006
	Belmont MI 49306 USA	Signature of Preparer (optional)	

### Section II - Hazardous ingredients / Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Polyurethane (MOD)				100%

### Section III - Physical / Chemical Characteristics

Boiling Point	NA	Specific Gravity (H <sub>2</sub> O = 1)	1
Vapor Pressure (mm Hg.)	Negligible	Melting Point	NA
Vapor Density (AIR=1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	Negligible		
Appearance and Odor	White Magenta / Odorless		

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	NA – Combustible Solid	Flammable Limits	LEL NA	UEL NA
Extinguishing Media	Water Spray Dry Chemical			
Special Fire Fighting Procedures	Wear Self-contained Breathing Apparatus and Protective Clothing			
Unusual Fire and Explosion Hazards	NA			

**Section V - Reactivity Data**

Stability	NA	Unstable		Conditions to Avoid
		Stable	X	
Incompatibility ( <i>Materials to avoid</i> )	Material can react with strong Oxidizing Agents			
Hazardous Decomposition or Byproducts	Carbon Dioxide, Carbon Monoxide			
Hazardous Polymerization	May Occur		Conditions to Avoid	
	Will not Occur	X		

**Section VI - Health Hazard Data**

Route(s) of Entry:	NA	Inhalation?	NA	Skin?	NA	Ingestion?	NA
Health Hazards (Acute and Chronic)	NA - Molten material will burn, cool quickly						
Carcinogenicity:	NA	NTP?		IARC Monographs?		OSHA Regulated?	
Signs and Symptoms of Exposure	NA						
Medical Conditions Generally Aggravated by Exposure	NA						
Emergency and First Aid Procedures	Burns should be treated as Thermal Burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.						

**Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled	Sweep or Scoop up and Remove
Waste Disposal Method	Discharge, treatment, or disposal may be subject to national, state or local laws. Incinerate.
Precautions to Be Taken in Handling and Storing	None (practice good industrial hygiene)
Other Precautions	Avoid temperatures ABOVE 428° F

**Section VIII - Control Measures**

Respiratory Protection (Specify Type)			
Ventilation:	Local Exhaust	X	Special
	Flammable Limits		Other
Protective Gloves	Only to protect against burns		Eye Protection
Other Protective Clothing or Equipment	Minimize Eye Contact		
Work/Hygienic Practices	Only to protect against burns		
	Practice good industrial hygiene		