



LENDERINK TECHNOLOGIES

and Associates

1267 House St. NE, Belmont, MI 49306
(616) 887-8257 Fax (616) 887-7910 www.lenderink.com

Technical Data Sheet

Dry Film Adhesive 486 N - The **ULTIMATE PSA!**

*≈ **THE VERY BEST - INDOOR / OUTDOOR** ≈*

WATERPROOF

! SUPERIOR ADHESION STRENGTH !

2 - SIDED **PRESSURE SENSITIVE ADHESIVE**

CAN BE APPLIED AT: -10 TO 60° C

14 TO 140° F

EXTREME LONG TERM DURABILITY

PRESSURE - 16 psi

GOOD WORKABILITY ≈ CLEAN - EASY HAND CUTTING - No OOZE or SQUEEZE OUT

ENVIRONMENT FRIENDLY: No TOLUENE - No FORMALDEHYDE - No XYLENE

HEAT RESISTANCE 300° F / 148° C +

.010" THICKNESS / ADHESIVE = ACRYLIC
< BASE = POLYETHYLENE (WOVEN)
\ ADHESIVE = ACRYLIC

.014" WITH RELEASE LINER

ROLL: 4' W x 66' L

SLITTING & SHEETING AVAILABLE

PERMANENT BOND TO:

METAL, WOOD, PLASTIC, GLASS, FOAM, HONEYCOMB, CERAMIC, STONE, ETC.....

Rev. 4/17/2020