



LENDERINK
TECHNOLOGIES INC.

A640R Retardant Petro Bond

⚙ **Bonds petroleum liquids into a solid mass** ⚙

A640R PETRO BOND is an environmentally friendly petroleum-bonding agent designed to solidify petroleum-based spills. Petroleum-based products include oils, fuels, solvents, etc.

- **Non-toxic**
- **Non-hazardous**
- **Non-corrosive**

A dry granular material that bonds petroleum-based liquids and other liquids into a solid mass. These liquids include oils, fuels, solvents and paints. A640R bonds these materials with little increase in volume.

Not only does A640R Retardant Petro Bond solidify the petroleum-based spill, it also contains a fire retardant to reduce flammability.

The amount of A640R used depends on the degree of solidification desired and the viscosity of the liquid being bonded. One pound of A640R to 3.5 pounds of spilled liquid is normal.

COMPLIANCE: Solidified or gelled materials must be disposed of in accordance with federal, state, and local laws and regulations. The user is solely responsible for compliance with disposal of solidified or gelled materials.

APPLICATION: Dry powder material for use to immobilize petroleum based liquids (on water or land) including fuels, solvents, paints, etc. Suitable to bond or congeal a spill - to slow or stop the spread of the liquid.

TOXICITY: This product is non-toxic, non-hazardous, non-corrosive; see Material Safety Data Sheet.

STORAGE SPECIFICATIONS: Keep free of contamination.

FLASH POINT: N/A

VOLATILITY BEFORE USE: None

VOLATILITY AFTER USE: Varies with the flammability of the liquid being bonded.

Contact Lenderink today for more information!

Visit us at www.lenderink.com

Email: Sales@Lenderink.com