



LENDERINK
TECHNOLOGIES INC.

A650 Petro Bond

☼ **Congeals and Bonds Water-Borne Petroleum Based Spills** ☼

A650 PETRO BOND is an environmentally friendly petroleum-solidifying agent primarily for water-borne spills. Petroleum-based products include oils, fuels, solvents, paints, etc.

- * **Non-toxic**
- * **Non-hazardous**
- * **Non-corrosive**
- * **Odorless**

A dry granular material specifically designed to immobilize petroleum-based liquid spills on land by solidifying the liquid. Unlike absorbents that soak up the liquid through expansion, A650 bonds the liquid into a solid carpet-like mass, with minimal volumetric increase and retains the liquid for easier removal. This will reduce wildlife loss. A650 eliminates the dripping sponge effect by not allowing the liquid to be squeezed out and minimizes any residue or contamination.

A unique feature of A650 is that while solidifying the petroleum-based spill into a solid carpet-like mass, it does not pick up any water in the process. This allows A650 to be used on land for preventative measures prior to a possible spill. For example, a trench around a petroleum storage area or under an in-ground tank could be filled with A650 to prevent ground contamination in case of a leak.

METHOD OF DISPOSAL:

Extreme caution must be exercised when handling, storing and disposing of solidified or gelled hazardous materials.

COMPLIANCE: Solidified or gelled materials must be disposed of in accordance with federal, state and local laws and regulations. The user is solely responsible for compliance with disposal laws and regulations; the manufacturer or seller assumes no responsibility for the proper or improper disposal or solidified or gelled materials.

APPLICATION: Dry powder material for use in immobilizing petroleum-based liquids on land, including fuels solvents, paints, etc. The product is suitable to bond or congeal a spill to slow or stop the spread of the liquid.

WEIGHT BY VOLUME: One (1) pound equals 114 cubic inches.

SPECIFIC GRAVITY: .91

PH SPECIFICATIONS: Neutral (6.5 to 7)

TOXICITY: This product is non-toxic, non-hazardous, non-corrosive.

STORAGE SPECIFICATIONS: Keep free of contamination.

FLASH POINT: N/A

VOLATILITY BEFORE USE: None

VOLATILITY AFTER USE: Varies with the flammability of the liquid being bonded.

Contact Lenderink today for more information!

Visit us at www.lenderink.com

Email: Sales@Lenderink.com